

16 AWG 2 Solid Conductors Shielded Riser

Part Number: 4406

Ratings FPLR, CL3R, FT4, Sunlight Resistant

Approvals UL Listed

Construction

Conductor Type 16 AWG Solid Bare Copper

Conductor Count 2

Insulation Colors Black, Red

Insulation Type Polypropylene

Insulation Thickness 0.008" nom.

Cable Lay Length 2.75" nom.

Shielding Aluminum Foil/Mylar

Rip Cord Yes

Jacket Material PVC

Jacket Thickness 0.015" nom.

Overall Outer Diameter 0.176" nom.

Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)

Print Legend HONEYWELL P/N 4406 2C 16AWG SHIELDED E175105 (UL) FPLR OR CL3R FT4 SUN RES 75C
(RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

Electrical & Environmental

Temperature -20°C to 75°C

Voltage 300V max.

Capacitance 41.7 pF/ft. nom.

Impedance 37 Ohms nom.

DC Resistance 4.1 Ohms/1000' at 20°C

RoHS Compliant Yes